

Centro Tessile Serico Sostenibile Srl

via Castelnuovo, 3 - 22100 Como Italia Pho +39 031 3312111/120 Fax: +39 0313312149 Amministrazione/Contabilità +39 031 3312102-154

P. IVA - C.F. 003900470133 Capitale sociale euro 600000,00 iv mailbox@textilecomo.com www.textilecomo.com

Test Report No.: 2104174-001

16-lug-21 Date Test Report

2104174 Acceptance:

Arrival date sample 04-giu-21 Start date test 04-giu-21 End date test 15-lug-21

References:

Sampling Mode:

Customer Code 08424

Dear:

ZIMMER + ROHDE GmbH Zimmersmühlenweg 14-18 61440 Oberursel Deutschland

Mrs Oda Nimmer

Phone:

[C] Item: 10911

[C] Declared Compostion: 100% Polyester FR

Sampling by Customer

Curtains [C] End use: Fabric Typology: Return: No request

Test Results

Test	Method	U.M.	Result
15246 FLAMMABILITY REQUIREMENTS FOR FABRICS CURTAINS, DRAPES AND WINDOW BLINDS (type A - B)	BS 5867-2:2008		
Instrument: Rhoburn Tester			
Pretreatment carried out			none
Test method used			type B
Tested sample surface:			face of fabric
Dimension of specimens:		mm	200 x 160
Type of ignition used:			surface ignition
Time of application of flame:		S	15
Number of tests specimens			6
TEST RESULT			SAMPLE MEETS THE BS 5867- 2:2008 (Type B) REQUIREMENTS
Deviations from the method			none
Annex n.			1F
Details of the test results related to each specimen can	be seen in the annex of this test report.		
15426 FLAMMABILITY REQUIREMENTS FOR FABRICS CURTAINS, DRAPES AND WINDOW BLINDS (type C)	BS 5867-2:2008		•
Instrument: Rhoburn Tester			
Pretreatment carried out			none
Test method used			type C
Tested sample surface:			face and back of fabric
Dimension of specimens:		mm	200 x 160
Type of ignition used:			surface ignition

The Results contained in this Report refer only to the Sample as received and do not imply an approval of the tested product by the Laboratory of the Centro Tessile Serico Sostenibile Srl. Unless otherwise specified, the side examined / straight of use is indicated by the Customer: this information can influence the results of the tests and therefore the Test Laboratory declines all responsibility.

This Report may not be reproduced in part, unless written permission of Centro Tessile Serico Sostenibile Srl Laboratory.

[C] = Information provided by the Customer, of which the Centro Tessile Serico Sostenibile Srl Laboratory declines all responsibility.



Centro Tessile Serico Sostenibile Srl

via Castelnuovo, 3 - 22100 Como Italia Pho +39 031 3312111/120 Fax: +39 0313312149 Amministrazione/Contabilità +39 031 3312102-154

P. IVA - C.F. 003900470133 Capitale sociale euro 600000,00 iv mailbox@textilecomo.com

Test Report No.:

Type of ignition used:

TEST RESULT

Time of application of flame:

Number of tests specimens

Deviations from the method

2104174-001

Test	Method	U.M.	Result
Time of application of flame:		S	5, 10, 20 and 30
Number of tests specimens			16
Deviations from the method			none
Annex n.			2F
Details of the test results related to each specimen can b	e seen in the annex of this test report.		
25165 WASHING TREATMENTS	UNI EN ISO 10528:1997		•
Instrument: WASHING-MACHINE ELECTROLUX	WASCATOR mod. FOM 71 CLS		
Programme of washing: 3N - normal agitation Test Temperature:30°C Drying procedure: type C - Flat dry Detergent used: ECE (ref.A) - Sodium Perborated - TAED Total air-dry- mass (specimens and ballast): 2,0 kg Type of ballast used: Type III (polyester) Number of washings performed: 50			
THE SAMPLE, TREATED AS ABOVE DESCRIBED, HAS BEEN	SUBMITTED TO NEXT TEST.		
15426 FLAMMABILITY REQUIREMENTS FOR FABRICS CURTAINS, DRAPES AND WINDOW BLINDS (type C)	BS 5867-2:2008		
Instrument: Rhoburn Tester			
Pretreatment carried out			5 washing cycles at 30°C, as above described
Test method used			type C
Tested sample surface:			face and back of fabric
Dimension of specimens:		mm	200 x 160

The Results contained in this Report refer only to the Sample as received and do not imply an approval of the tested product by the Laboratory of the Centro Tessile Serico Sostenibile Srl. Unless otherwise specified, the side examined / straight of use is indicated by the Customer: this information can influence the results of the tests and therefore the Test Laboratory declines all responsibility.

This Report may not be reproduced in part, unless written permission of Centro Tessile Serico Sostenibile Srl Laboratory.

[C] = Information provided by the Customer, of which the Centro Tessile Serico Sostenibile Srl Laboratory declines all responsibility.

Details of the test results related to each specimen can be seen in the annex of this test report.

surface ignition

5, 10, 20 and 30

16

SAMPLE MEETS THE BS 5867-2:2008 Type C REQUIREMENTS

none



Centro Tessile Serico Sostenibile Srl

via Castelnuovo, 3 - 22100 Como Italia Pho +39 031 3312111/120 Fax: +39 0313312149 Amministrazione/Contabilità +39 031 3312102-154

P. IVA - C.F. 003900470133 Capitale sociale euro 600000,00 iv mailbox@textilecomo.com

Test Report No.:	2104174-001

Test	Method	U.M.	Result
			The Laboratory Manager Fausto Albonico

END OF REPORT

The Results contained in this Report refer only to the Sample as received and do not imply an approval of the tested product by the Laboratory of the Centro Tessile Serico Sostenibile Srl. Unless otherwise specified, the side examined / straight of use is indicated by the Customer: this information can influence the results of the tests and therefore the Test Laboratory declines all responsibility.

This Report may not be reproduced in part, unless written permission of Centro Tessile Serico Sostenibile Srl Laboratory.

[C] = Information provided by the Customer, of which the Centro Tessile Serico Sostenibile Srl Laboratory declines all responsibility.