



Date of Issue: 3/28/2023 Report Number: 23-000984

Revision Number:1

Date Order Received: 03/24/2023

For the Account of: Zimmer & Rohde Germany Zimmersmuhlenweg 14-18

61440 Oberursel Germany

| Client's | Identification: | 10940 |
|----------|-----------------|-------|

CERTIFICATE OF TESTING

TEST PERFORMED: NFPA 701 Standard Methods of Fire Test for Flame Propagation of Textiles and Films 2019 – Test #1

TEST RESULTS

| Specimen | Mass Initial (g) | Mass Final (g) | Mass Loss (%) | Drip Burn (s) | Afterflame (s) |
|----------|------------------|----------------|---------------|---------------|----------------|
| 1 | 12.9 | 9.3 | 28 | 0.0 | 0.0 |
| 2 | 12.8 | 9.6 | 25 | 0.0 | 0.0 |
| 3 | 12.8 | 9.4 | 27 | 0.0 | 0.0 |
| 4 | 12.5 | 9.3 | 26 | 0.0 | 0.0 |
| 5 | 13.0 | 9.4 | 28 | 0.0 | 0.0 |
| 6 | 12.8 | 11.3 | 12 | 0.0 | 0.0 |
| 7 | 13.0 | 9.9 | 24 | 0.0 | 0.0 |
| 8 | 12.9 | 10.8 | 16 | 0.0 | 0.0 |
| 9 | 12.9 | 12.5 | 3 | 0.0 | 0.0 |
| 10 | 13.0 | 10.8 | 17 | 0.0 | 0.0 |
| Average | 12.9 | 10.2 | 21 | 0.0 | 0.0 |

| Approximate weight (oz./sq. yd): 6.3 | | Standard Deviation: 8.4 | Average + 3 SD: 46.2 | | | | |
|---|---|---|--|--|--|--|--|
| Product Configuration: Single Layer Conditioning: Oven at 220°F Intended End-use (if known & other than drapery): | | ☐ Multi Layer for minimum 30 minutes rapery | ☐ 70 ±2°F & 65 ±2%RH for minimum 24 hours | | | | |
| Where fragme seconds per s Where the ave Individual spec Where the specific be recorded as | CCEPTANCE CRITERIA terflame is required to be recorded; however, it is not factored into the Acceptance Criteria Where fragments or residues of specimens that fall to the floor of the test chamber continue to burn for more than an average of 2 seconds per specimen for the sample of 10 specimens, the material shall be recorded as failing. (Flaming Drip) Where the average weight loss of the 10 specimens in a sample is greater than 40 percent, the material shall be recorded as failing. Individual specimens will be listed as a failure if it exceeds mean + 3 SD Where the specimens do not demonstrate performance in accordance with either of the conditions indicated above, the material shall be recorded as passing this test and shall be designated as flame resistant. | | | | | | |
| _ | Complies Does Not Comply | | | | | | |
| specified by the standard | | btained after testing specimen in | accordance with the procedures and equipment | | | | |
| Berta Stiver | | | | | | | |
| Authorized Signature | | | Date Order Completed: 03/28/2023 | | | | |

553 76th Street, Byron Center, MI 49315

P: 616-559-6123 E: testlab@applied-lab.com

Page 1 of 1