



Date of Issue: 10/13/2025 Report Number: 25-002985

Revision Number:1

Date Order Received: 10/10/2025

For the Account of: Zimmer & Rohde Germany Zimmersmuhlenweg 14-18

61440 Oberursel

Germany

OI: 11	
Client's	Identification:

10979 MILETUS

CERTIFICATE OF TESTING

TEST PERFORMED: NFPA 260 Standard Methods of Tests and Classification System for Cigarette Ignition Resistance of Components of Upholstered Furniture – 2024; Fabric Cover Test

TEST RESULTS

Specimen	Char Length (in)	Extinguished in 45 Minutes
1	0.6	Yes
2	0.5	Yes
3	0.6	Yes

NOTES

Test Conditions: 70 \pm 4°F, 65 \pm 5% Relative Humidity **Test Environment:** 70 \pm 4°F, 50 \pm 5% Relative Humidity

Sampling: As Received Ignition Source: SRM 1196a

Abbreviations: SE = Self-extinguished OBV = Obvious ignition of substrate

ACCEPTANCE CRITERIA

- 1. If the test specimen has no ignition, or if no individual specimen yields a vertical char of 45 mm (1.75 inches) or greater, the fabric is classified a Class I cover fabric.
- 2. If the vertical char of any test specimen is greater than 45 mm (1.75 inches), the fabric is classified a Class II cover fabric.
- 3. If the smoldering extends beyond 45 minutes after placement of the cigarette, the fabric is classified as a Class II cover fabric
- 4. If an obvious ignition of the polyurethane substrate occurs on the test assembly, the fabric is classified a Class II cover fabric.

CONCLUSION	Based on the above Results and Acceptance Criteria, the item tested is ⊠ Class I □ Class II	5:
	TION I certify that the above results were obtained after testing specimen in act the standard stated above.	ccordance with the procedures and equipment
Berta S	Stiven	
Authorized Signa	nature	Date Order Completed: 10/13/2025