

For the Account of Zimmer & Rohde Germany
Zimmersmuhlenweg 14-18
61440 Oberursel Germany

Client's Identification 15533 RIFLESSO

CERTIFICATE OF TESTING

TEST PERFORMED Smolder Resistance of Materials Used in Upholstered Furniture - Section 1: Cover Fabrics California
Technical Bulletin 117-2013 (January 2019 Revision)

TEST RESULTS

	Specimen	Char Length (in)	Extinguished in 45 Minutes
Initial Test	1	0.4	Y
	2	0.5	Y
	3	0.5	Y

NOTES

Test Conditions 70 ±5°F, 50 ±5% Relative Humidity *Requirement 70±5°F, less than 55% Relative Humidity*
Sampling As Received
Ignition Source SRM 1196a
Abbreviations SE = Self-extinguished OBV = Obvious ignition of substrate

ACCEPTANCE CRITERIA

A material is considered to pass or fail based on the following criteria:

- A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:
 - The mock-up test specimen continues to smolder after the 45 minute test duration
 - A vertical char length of more than 1.8 inches (45mm) develops on the cover fabric
 - The mock-up test specimen transitions to open flaming
- The cover fabric passes the test if three initial mock-up specimens pass the test, i.e. the cigarettes burn their full length and are no longer smoldering
- If more than one initial specimen fails, the cover fabric fails the test
- If any one of the three initial specimens fails, repeat the test on additional three specimens
- If all three additional specimens pass the test, the cover fabric passes the test. If any one of the additional three specimens

CONCLUSION Based on the above Results and Acceptance Criteria, the item tested is:
☒ Pass
☐ Fail

CERTIFICATION I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

Berta Stiver

Authorized Signature

Date Order Completed: 05/28/2026