

Confidential Report

Our Ref: 23/60420F2/11/22







Client:

Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.

Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

Date: 5 December 2022

Our Ref: 23/60420F2/11/22

Your Ref: ---

Page: 1 of 4

Zimmer + Rohde GmbH

Zimmersmuhlenweg 14-18 61440 Oberursel Frankfurt Germany

Job Title: Fire Test on One Fabric Sample

Clients Order Ref: --

Date of Receipt: 25 November 2022

Date Test Started: 5 December 2022

Description of Sample: One sample of fabric, which was referenced by the client as;

19606, stated to be 88%PP 12%PES

Work Requested: We were asked to make the following fire test:

BS EN 1021:Part 1:2014 – Ignitability of Upholstered Furniture

- * subcontracted test, UKAS accredited
- ** subcontracted test, EN ISO/IEC 17025 accredited
- *** not UKAS accredited





Note: This report relates only to the items tested.



Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.

Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

Date: 5 December 2022

Our Ref: 23/60420F2/11/22

Your Ref:

Page: 2 of 4

Client: Zimmer + Rohde GmbH

FIRE TESTS ACCORDING TO BS EN 1021-1:2014

Assessment of the ignitability of upholstered furniture. Part 1. Ignition Source 1: Smouldering cigarette.

Pre-Treatment

The material received no pre-treatment as the fabric is stated not to be FR treated.

Conditioning

The materials for testing to Source 0 and 1 were conditioned for a minimum of 24 hours and tested in the environments specified in Clause 7 of BS EN 1021-1 & 2:2014.

The sample was tested in a room of volume 25m³ and 18°C.

Procedure

The test was carried out in accordance with BS EN 1021-2:2014. The sponsor sampled the material and the specimens were cut from the sample received to the dimensions set out in the standard.

The sample was tested over non-fire retardant polyurethane foam with a density of approximately 20-22 kg/m³.

Tests were made using ignition source 1.

Requirements

The specimens shall not:-

Smouldering Criteria

- display escalating combustion requiring active extinction. a)
- smoulders until it is essentially consumed within the test duration. b)
- smoulder to the extremities of the specimen, or through the full thickness, within the duration of the test. c)
- d) smoulder for more than one hour.
- show evidence of charring, other than discolouration, for more than 100mm in any direction apart from the e) nearest part of the original position of the source.







Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.

Page:

Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

5 December 2022 Date:

Our Ref: 23/60420F2/11/22 Your Ref:

3 of 4

Client: Zimmer + Rohde GmbH

Requirements (Continued)

Flaming Criteria

show evidence of flaming initiated by a smouldering source. a)

Results

| | Specimen No. | | |
|---|--------------|----|----------------|
| Smouldering criteria | 1 | 2 | 3 ¹ |
| Unsafe escalating combustion | No | No | |
| Testing assembly consumed | No | No | |
| Smoulders to extremities/full thickness | No | No | |
| Smoulders more than 1 hour | No | No | |
| In final examination, presence of progressive | No | No | |
| smouldering | | | |

| Flaming criteria | 1 | 2 | 3 ¹ |
|--|----|----|----------------|
| Occurrence of flames | No | No | |
| Specimen Result Ignition (I) / Non Ignition (NI) | NI | NI | |

Note

The test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.







Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.

Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

5 December 2022 Date:

Our Ref: 23/60420F2/11/22

Your Ref:

Page: 4 of 4

Zimmer + Rohde GmbH Client:

Comment

An NI designation indicates that the sample meets the performance requirements of BS EN 1021-1.

Where required to make a judgement to any pass/fail criteria an estimation of uncertainty of measurement has been taken into account. Under our Policy we have used a non-binary decision rule.

See our decision rules Policy (https://www.bttg.co.uk/about-us/decision-rules-policy/) for further information.

Uncertainty Budget

The overall uncertainty budget for BS EN 1021: Part 1:2014 is as follows:-

±2 seconds. Timings:

...... B Bland, Technical Customer Services Officer Reported by:.....

..... P Doherty, Manager Countersigned by:.....

Enquiries concerning this report should be addressed to Customer Services.



