



Date of Issue: 12/9/2022  
Report Number: 22-004028  
Revision Number: 1  
Date Order Received: 12/05/2022

For the Account of: Zimmer & Rohde Germany  
Zimmersmuhlenweg 14-18  
61440 Oberursel  
Germany

Client's Identification: 19607

## CERTIFICATE OF TESTING

**TEST PERFORMED:** California Technical Bulletin 117: June 2013 – Requirements, Test Procedure and Apparatus for Testing the Smolder Resistance of Materials Used in Upholstered Furniture – Cover Fabric Test

### TEST RESULTS

	Specimen	Char Length (in)	Extinguished in 45 Minutes
Initial Test	1	0.8	Y
	2	0.7	Y
	3	0.8	Y

### NOTES

**Test Conditions:** 70 ±5°F, 50 ±5% Relative Humidity

### ACCEPTANCE CRITERIA

A material is considered to pass or fail based on the following criteria:

- A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:
  - The mock-up test specimen continues to smolder after the 45 minute test duration
  - A vertical char length of more than 1.8 inches (45mm) develops on the cover fabric
  - The mock-up test specimen transitions to open flaming
- The cover fabric passes the test if three initial mock-up specimens pass the test, i.e. the cigarettes burn their full length and are no longer smoldering
- If more than one initial specimen fails, the cover fabric fails the test
- If any one of the three initial specimens fails, repeat the test on additional three specimens
- If all three additional specimens pass the test, the cover fabric passes the test. If any one of the additional three specimens fails, the cover fabric fails the test

**CONCLUSION** Based on the above Results and Acceptance Criteria, the item tested is:

- ☒ Pass  
☐ Fail

**CERTIFICATION** I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

Berta Stiver

Authorized Signature

Date Order Completed: 12/09/2022